

# M-Bus Master on a view



## Central Unit 250 - Art. No.: DR001

- M-Bus data logger for 250 slaves
- Operation on-site by keyboard and LCD
- Export of measured data to PC database
- Service and modem interface

### Technical data:

- 85 x 200 x 240mm
- Wall mounted
- RS232C
- external Modem (e.g. MOD001)
- external plug-in or wall mounted power supply (scope of supply)
- 512kB memory



## Central Unit 120 - Art. No.: DR002

- M-Bus data logger for 120 slaves
- Operation on-site by keyboard and LCD
- Export of measured data to PC database
- Service and modem interface

### Technical data:

- 85 x 200 x 240mm
- Wall mounted
- RS232C
- external Modem (e.g. MOD001)
- external plug-in or wall mounted power supply (scope of supply)
- 512kB memory



## W60 Data Logger - Art. No.: MR004DL

- M-Bus data logger for 60 slaves
- Level converter for 60 slaves
- Operation on-site by keyboard and LCD
- Integrated 230V power supply

### Technical data:

- 71 x 165 x 175mm
- Wall mounted
- RS232C and RS485
- external modem (e.g. MOD001)
- integrated 230V or 110V power supply
- 512kB memory



## W60 Remote Display - Art. No.: MR004FA

- M-Bus remote display for 60 slaves
- Level converter for 60 slaves
- Operation on site by keyboard and LCD
- Integrated 230V power supply

### Technical data:

- 71 x 165 x 175mm
- Wall mounted
- RS232C and RS485
- external modem
- integrated 230V or 110V power supply



## C20 Data Logger - Art. No.: MR006DL

- M-Bus Data logger for 20 slaves
- Level converter for 20 slaves
- Operation on-site by keyboard and LCD
- Rail mounted

### Technical data:

- 58 x 106 x 96mm
- Mounted on DIN rail TS35
- RS232C
- external modem (e.g. MOD001)
- external 24V power supply (not in scope of supply)
- 1MB memory
- optional 2MB/4MB



## C20 Remote Display - Art. No.: MR006FA

- M-Bus remote display for 20 slaves
- Level converter for 20 slaves
- Operation on-site by keyboard and LCD
- Rail mounted

### Technical data:

- 58 x 106 x 96mm
- Mounted on DIN rail TS35
- RS232C
- external modem
- external 24V power supply (not in scope of supply)



## C3 Data Logger - Art. No.: MR005DL

- M-Bus Data logger for 3 slaves
- Level converter for 3 slaves
- Operation on-site by keyboard and LCD
- Rail mounted

### Technical data:

- 58 x 106 x 96mm
- Mounted on DIN rail TS35
- RS232C
- external modem (e.g. MOD001)
- external 24V power supply (not in scope of supply)
- 1MB memory
- optional 2MB/4MB



## C3 Remote Display - Art. No.: MR005FA

- M-Bus remote display for 3 slaves
- Level converter for 3 slaves
- Operation on-site by keyboard and LCD
- Rail mounted

### Technical data:

- 58 x 106 x 96mm
- Mounted on DIN rail TS35
- RS232C
- external modem
- external 24V power supply (not in scope of supply)

# M-Bus Level converter on a view



## **Art.No.: DR003 - Art. No.: DR004**

- M-Bus level converter for 250 / 120 slaves
- RS232C interface

### **Technical data:**

- 85 x 200 x 240mm
- Wall mounted
- RS232C

- external plug-in or wall mounted power supply (scope of supply)



## **Art.No.: DR005 - Art. No.: DR006**

- M-Bus level converter for 250 / 120 slaves
- RS485 interface

### **Technical data:**

- 85 x 200 x 240mm
- Wall mounted
- RS485

- external plug-in or wall mounted power supply (scope of supply)



## **Repeater - Art. No.: DR007**

- M-Bus repeater for 250 slaves
- Increases the number of slaves by 250
- Increases the M-Bus extension (cable)

### **Technical data:**

- 85 x 200 x 240mm
- Wall mounted
- external plug-in power supply (scope of supply)



## **Micromaster - Art. No.: MR003 / MR003 USB**

- Portable M-Bus level converter for 10 slaves
- Power supply by laptop
- Versions with RS232C or USB interface available

### **Technical data:**

- 30 x 54 x 110mm
- RS232C or USB interface
- Power supply by laptop

Delivery contains:

- MR003:** special cable
- MR003USB:** USB cable
- Device driver for Windows



## **W60 Level Converter - Art. No.: MR004W**

- M-Bus level converter for 60 slaves
- RS232C and RS485 interface
- Integrated power supply

### **Technical data:**

- 71 x 165 x 175mm
- Wall mounted
- RS232C
- external modem

- integrated 230V or 110V power supply



## **PW60 - Art. No.: MR004C**

- M-Bus level converter for 60 slaves
- RS232C and RS485 interface
- IR-opto-interface

### **Technical data:**

- 78 x 70 x 118mm
- Mounted on DIN rail TS35
- RS232C, RS485 and IR-opto-interface

- external plug-in power supply (not in scope of supply)



## **PW20 - Art. No.: MR006**

- M-Bus level converter for 20 slaves
- RS232C and RS485 interface
- IR-opto-interface

### **Technical data:**

- 78 x 70 x 118mm
- Mounted on DIN rail TS35
- RS232C, RS485 and IR-opto-interface

- external plug-in power supply (not in scope of supply)



## **PW3 - Art. No.: MR005**

- M-Bus level converter for 3 slaves
- RS232C and RS485 interface
- IR-opto-interface

### **Technical data:**

- 78 x 70 x 118mm
- Mounted on DIN rail TS35
- RS232C, RS485 and IR-opto-interface

- external plug-in power supply (not in scope of supply)



Reinecke Elektronikentwicklung und Layout GmbH  
Stettiner Str. 38  
D-33106 Paderborn  
www.relay.de

Tel.: 05251 / 1767-0  
Fax.: 05251 / 1767-20  
E-Mail: info@relay.de



Meß- und Kommunikationstechnik GmbH  
Stettiner Str. 38  
D-33106 Paderborn  
www.padmess.de

Tel.: 05251 / 1769-0  
Fax.: 05251 / 1769-20  
E-Mail: info@padmess.de